




# Seastar Series



-   
for Above  
Ground Pools
-   
Unique Designed  
Appearance
-   
Integrated  
Controller
-   
Quiet?
-   
Plug and Play
-   
Compact  
Structure
-   
Portable



## Mini Swimming POOL Heat Pump

Ambient Temperature: (DB/WB) 27°C/24.3°C; Water Inlet/Outlet Temperature: 26°C/28°C.

Heating Capacity (kW)	3	5
Power Input (kW)	0.57	0.9
COP	5.2	5.55

Ambient Temperature: (DB/WB) 15°C/12°C; Water Inlet Temperature: 26°C.

Heating Capacity (kW)	2.2	3.6
Power Input (kW)	0.53	0.837
COP	4.1	4.3

Power Supply (V/Ph/Hz)	220-240V / 1Ph / 50Hz	
Max. Power Input (kW)	0.9	1.5
Max. Current (A)	4.1	7.1
Operating Temperature Range (°C)	5-43	5-43
Heating Temperature Range (°C)	10-40	10-40
Refrigerant Type	R32 / R410A	
Compressor Brand	LANDA (Gree) or GMCC (Midea)	
Sound Pressure at 1m dB(A)	44	33
Water Flow (m³/h)	1.5	2.15
Water Pressure Drop (kPa)	10	15
Net Dimensions (L*W*H) (mm)	425*290*431	505*360*545
Net Weight (kg)	19	28
Water Pipe Connection (mm)	32 or 38	32 or 38

Notice:

The above data is for reference only, the specific data is subject to actual product.

Lazord Pool & Spa Equipment

☎ 0792102828 ✉ Lazordpool@gmail.com/Nael2020@gmail.com 📍 Amer bin malik st b72